



PRO-ATT ... dB-2-3-N

Attenuator 2 W



DESCRIPTION

- This 2 W series includes 3 dB, 6 dB, 10 dB, 20 dB and 30 dB attenuators.
- This series of attenuators has very low VSWR and attenuation flatness and is especially suitable for use with:
 - Coaxial Transmission Lines
 - Power Monitors
 - Watt Meters

SPECIFICATION

ELECTRICAL

Frequency	DC – 3 GHz
Max. Input Power	2 W
Impedance	50 Ω
Attenuation	See table below
VSWR	< 1.25:1

ENVIRONMENTAL

Operating temperature range	-35 °C to +70 °C
-----------------------------	------------------

MECHANICAL

Connection(s)	N(m) to N(f)
Historic Brand	Amphenol Procom
Dimensions	Approx. 53 x 21 mm / 2.09 x 0.83 in.
Weight	Approx. 0.071 kg / 0.16 lb.

ORDERING CODES

Model	Product No.	Model
PRO-ATT 3 dB-2-3-N	200002212	PRO-ATT 3 dB-2-3-N
PRO-ATT 6 dB-2-3-N	200002213	PRO-ATT 6 dB-2-3-N
PRO-ATT 10 dB-2-3-N	200002087	PRO-ATT 10 dB-2-3-N
PRO-ATT 20 dB-2-3-N	200002214	PRO-ATT 20 dB-2-3-N
PRO-ATT 30 dB-2-3-N	200002215	PRO-ATT 30 dB-2-3-N

ADDITIONAL INFORMATION

Additional Data

MODEL	ATTENUATION	ATT. DEVIATION	
		DC – 2.0 GHz	2.0 – 3.0 GHz
PRO-ATT 3 dB-2-3-N	3 dB	+/-0.2 dB	+/-0.3 dB
PRO-ATT 6 dB-2-3-N	6 dB	+/-0.2 dB	+/-0.3 dB
PRO-ATT 10 dB-2-3-N	10 dB	+/-0.2 dB	+/-0.3 dB
PRO-ATT 20 dB-2-3-N	20 dB	+/-0.2 dB	+/-0.3 dB
PRO-ATT 30 dB-2-3-N	30 dB	+/-0.5 dB	+/-1.5 dB

