



GA 2/...-FME

Rubber Antenna with Universal FME-Connection System for Portable Equipment in the 2 m Band



DESCRIPTION

- Sturdy, conical, flexible rubber antenna
- Full size $\frac{1}{4} \lambda$ whip.
- Highest quality materials – designed for “wear and tear”.
- Delivered factory tuned and tested to ensure minimum VSWR and optimum performance.
- Provided with universal FME-connection system for optimum flexibility and easily exchangeable connectors.
- Designed for use with the following of Procoms line of black FME-connectors (to be ordered separately): BFME-UHF, BFME-BNC, BFME-TNC, BFME-N, BFME-EBNC and BFME-ETNC.

SPECIFICATION

Last Update: 07/10/2026 07:09 AM

ELECTRICAL

Model	GA 2/...-FME
Frequency	2 m band covered by two models
Antenna Type	$\frac{1}{4}$ λ antenna for portable equipment
Max. Input Power	100 W
Polarisation	Vertical
Impedance	50 Ω
Gain	0 dB (compared to a $\frac{1}{4}$ λ portable antenna)
VSWR	< 2.0:1 when mounted directly on portable equipment
Bandwidth	≥ 20 MHz @ VSWR ≤ 2.5

MECHANICAL

Connection(s)	FME(f) (Exchangeable BFME-connectors to be ordered separately)
Materials	Steelwire moulded in thermoplastic rubber Black-chromed brass
Colour	Black
Historic Brand	Amphenol Procom
Height	Approx. 450 mm / 17.72 in.
Weight	Approx. 0.06 kg / 0.13 lb.

ORDERING CODES

MODEL	PRODUCT NO.	FREQUENCY
GA 2/l-FME(f)	140000120	144 – 164 MHz
GA 2/h-FME(f)	140000116	155 – 175 MHz

ADDITIONAL INFORMATION

Recommended BFME-Connectors

BFME-UHF 	BFME-BNC 	BFME-TNC 	BFME-N 
BFME-EBNC 		BFME-ETNC 	

(To be ordered separately)

Please Note

The GA 2 is also available with SMA(m) connector and different thread studs, but in this case with fixed, non-exchangeable connector (not FME connection system). Information on these special versions on request.

