



FSP 70 1/4/...-SMA

"StraightFlex" Antenna with Universal SMA-Connection System for Portable Equipment in the 70 cm Band



DESCRIPTION

- Highly flexible, polyethylene covered Straight-Flex steel wire.
- Full-size $\frac{1}{4} \lambda$ whip.
- Highest quality materials in an elegant design.
- Delivered factory tuned and tested to ensure minimum VSWR.
- Designed for use with SMA-connector.

SPECIFICATION

ELECTRICAL

Model	FSP 70 1/4/...-SMA
Frequency	70 cm band covered by three models
Antenna Type	Antenna for portable equipment
Max. Input Power	100 W
Polarisation	Vertical
Impedance	50 Ω
Gain	0 dB (compared to a ¼ λ portable antenna)
VSWR	< 2.0:1 when mounted directly on portable equipment
Bandwidth	≥ 50 MHz @ VSWR ≤ 2.0

MECHANICAL

Connection(s)	SMA(m)
Materials	Polyethylene covered flexible steel wire Black-chromed brass
Colour	Black
Historic Brand	Amphenol Procom
Height	Approx. 223.5 mm / 8.80 in.
Weight	Approx. 0.025 kg / 0.06 lb.

ORDERING CODES

MODEL	PRODUCT NO.	FREQUENCY
FSP 70 1/4/s-SMA(m)	140000330	380 – 430 MHz
FSP 70 1/4/l-SMA(m)	140000371	400 – 450 MHz
FSP 70 1/4/h-SMA(m)	140000297	420 – 470 MHz

